







This old-fashioned tag with its slate design is ideal to bring a vintage and traditional touch to your communication. It can be used to print your texts and logos with Evolis white monochrome ribbon.

### **ADVANTAGES**

Using Evolis High Trust® cards allows an optimal printing quality and a good readability of specific elements (texts, barcodes...). They are flexible but very resistant and solid.

Additionally, our PVC cards are dedicated to use in the food industry, they are ideal for price tag labelling (bakers, butchers, supermarkets, etc.).

Tested and validated by Evolis R&D and Quality departments, these consumables bring you printing quality and reliability.

# **GENERAL SPECIFICATIONS**

- · Cards in PVC Preprinted Slate design Mirror finish
- $\cdot$  Compliant with ISO CR-80 (ISO 7810) standards
- Dimension: 85.6 mm Length x 54 mm Width (3 3/8" x 2 1/8")
- · Thickness: 0.76 mm / 30 mil



# PRODUCT INFORMATION:

- PVC Cards
- Preprinted Cards Slate design
- 30 MIL



### COMPATIBILITY AND PACKAGING

| PART | #  | PACKAGE               | ZENIUS /<br>PRMACY | EDIKIO ACCESS | EDIKIO FLEX | EDIKIO DUPLEX |
|------|----|-----------------------|--------------------|---------------|-------------|---------------|
| C900 | Ol | 1 box of 100<br>cards | •                  | •             | ٠           | •             |

# STORAGE INFORMATION

The cards shall be capable of functioning for up to 2/3 years after purchase if stored in a cool, dry environment and having remained unopened from the original packaging.

Temperature of storage must be between 15-30°C (and at RH between 10-60%).

Once opened, avoid dust, direct sunlight, high humidity and high temperatures.

Do not place near solvent or other chemicals.

### **INSTRUCTIONS FOR USE**

In order to optimize the printing quality and card durability:

- · Do not print cards that are damaged, folded, dirty or deformed.
- · Avoid touching the printable surface of the cards to preserve print quality.
- Do not expose tags to strong sources of heat (deterioration possible from 60  $^{\circ}$ C / 140  $^{\circ}$ F). Avoid thermal shocks.
- · Avoid putting the printed labels in contact with fatty substances.
- Do not clean the tags in a machine, with boiling water or abrasive detergent products.

  Preference should be given to cleaning with warm water (<60°C / 140°F) or with a neutral detergent diluted with water, and a microfibre cloth. Dry the tags thoroughly before using them.



